Revision 14

Supersedes date 29/10/2013

# SAFETY DATA SHEET AIBC ADD IT BRAKE CLEANER 500ML

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name AIBC ADD IT BRAKE CLEANER 500ML

Product No. SVTAE500BCL

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Brake Cleaner

## 1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited

Salmon Fields, Royton, Oldham, Lancashire, OL2 6HZ, England 0161 627 0101

sds@jamesbriggs.co.uk

## 1.4. Emergency telephone number

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Aerosol 1 - H222

Human health Skin Irrit. 2 - H315;Eye Irrit. 2 - H319;STOT SE 3 - H336

Environment Aquatic Chronic 2 - H411

Classification (1999/45/EEC) Xi;R36/38. F+;R12. N;R51/53. R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

P305+351+338

## 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

H222 Extremely flammable aerosol.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statements** 

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing vapour/spray.

P280 Wear protective gloves, eye and face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.
P337 If eye irritation persists:

P501 Dispose of contents/container in accordance with local regulations.

Supplementary	Precautionary	Statements
---------------	---------------	------------

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P264 Wash contaminated skin thoroughly after handling.
P321 Specific treatment (see medical advice on this label).
P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332+313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°

F.

#### 2.3. Other hazards

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

ACETONE		10-30%
CAS-No.: 67-64-1	EC No.: 200-662-2	

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 2 - H225 F;R11
EUH066 Xi;R36
Eye Irrit. 2 - H319 R66
STOT SE 3 - H336 R67

BUTANE 5-10%

CAS-No.: 106-97-8 EC No.: 203-448-7

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

ISOBUTANE 1-5%

CAS-No.: 75-28-5 EC No.: 200-857-2

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT 30-60%

CAS-No.: 64742-49-0 EC No.: 265-151-9 Registration Number: 01-2119475514-35-xxxx

Classification (EC 1272/2008) Classification (67/548/EEC)

 Flam. Liq. 2 - H225
 Xn;R65.

 Skin Irrit. 2 - H315
 Xi;R38.

 STOT SE 3 - H336
 F;R11.

 Asp. Tox. 1 - H304
 N;R51/53.

 Aquatic Chronic 2 - H411
 R67.

PROPAN-2-OL			10-30%
CAS-No.: 67-63-0	EC No.: 200-661-7		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Eye Irrit. 2 - H319		Xi;R36	
STOT SE 3 - H336		R67	

PROPANE

CAS-No.: 74-98-6

EC No.: 200-827-9

Classification (EC 1272/2008)
Flam. Gas 1 - H220

F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## **SECTION 4: FIRST AID MEASURES**

## 4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

## 5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

## 6.4. Reference to other sections

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

# 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE				500 ppm	1210 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
ISOBUTANE	WEL	800 ppm		800 ppm		
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT			1200 mg/m3	60 ppm	216 mg/m3	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	
PROPANE		Asphyxiating	Asphyxiating.	Asphyxiating	Asphyxiating.	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

Protective equipment





Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Characteristic.

Solubility Insoluble in water

Flammability Limit - Lower(%) 0.8
Flammability Limit - Upper(%) 9.0

#### 9.2. Other information

#### **SECTION 10: STABILITY AND REACTIVITY**

## 10.1. Reactivity

#### 10.2. Chemical stability

Stable under normal temperature conditions.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

#### Inaestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

## Eye contact

Irritating to eyes. May cause chemical eye burns.

Route of entry

Inhalation. Skin and/or eye contact.

## **SECTION 12: ECOLOGICAL INFORMATION**

### **Ecotoxicity**

Dangerous for the environment if discharged into watercourses.

#### 12.1. Toxicity

## 12.2. Persistence and degradability

## 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## **SECTION 14: TRANSPORT INFORMATION**

## 14.1. UN number

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

#### 14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 2.1

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels



## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



## 14.6. Special precautions for user

EMS F-D, S-U
Tunnel Restriction Code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Uk Regulatory References** 

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

**Guidance Notes** 

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

## 15.2. Chemical Safety Assessment

#### **SECTION 16: OTHER INFORMATION**

Revision Date 14/04/2014

Revision 14

Supersedes date 29/10/2013

Risk Phrases In Full

R12 Extremely flammable.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable

R36/38 Irritating to eyes and skin.

R36 Irritating to eyes.
R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H222 Extremely flammable aerosol.
H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H411 Toxic to aquatic life with long lasting effects.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.