

## SAFETY DATA SHEET

### H16 NILCO FOAMING GLASS CLEANER SRP 500ML

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product name H16 NILCO FOAMING GLASS CLEANER SRP 500ML  
Product No. SVTN500FGCSR

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Glass cleaner.

##### 1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited  
4, Howarth Court,  
Gateway Crescent, Chadderton,  
Oldham, Lancashire,  
OL9 9XB,  
England  
0161 627 0101  
sds@jamesbriggs.co.uk

##### 1.4. Emergency telephone number

#### SECTION 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Aerosol 1 - H222
Human health	Not classified.
Environment	Not classified.

Classification (1999/45/EEC) F+;R12.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

##### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word	Danger	
Hazard Statements	H222	
Precautionary Statements	Extremely flammable aerosol.	
	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P261	Avoid breathing vapour/spray.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements		
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

# H16 NILCO FOAMING GLASS CLEANER SRP 500ML

Supplemental label information

H229 Pressurised container: May burst if heated

## 2.3. Other hazards

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

2-BUTOXYETHANOL	1-5%
CAS-No.: 111-76-2	EC No.: 203-905-0
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xn;R20/21/22 Xi;R36/38
BUTANE	1-5%
CAS-No.: 106-97-8	EC No.: 203-448-7
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
ISOBUTANE	1-5%
CAS-No.: 75-28-5	EC No.: 200-857-2
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
PROPAN-2-OL	5-10%
CAS-No.: 67-63-0	EC No.: 200-661-7
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R67
PROPANE	5-10%
CAS-No.: 74-98-6	EC No.: 200-827-9
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

# H16 NILCO FOAMING GLASS CLEANER SRP 500ML

## General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

### Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

### Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

### Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## **4.2. Most important symptoms and effects, both acute and delayed**

## **4.3. Indication of any immediate medical attention and special treatment needed**

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### **5.2. Special hazards arising from the substance or mixture**

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

### **6.2. Environmental precautions**

### **6.3. Methods and material for containment and cleaning up**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

### **6.4. Reference to other sections**

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### **7.2. Conditions for safe storage, including any incompatibilities**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### **7.3. Specific end use(s)**

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1. Control parameters**

## H16 NILCO FOAMING GLASS CLEANER SRP 500ML

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-BUTOXYETHANOL	WEL	25 ppm(Sk)		50 ppm(Sk)		
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
ISOBUTANE	WEL	800 ppm		800 ppm		
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	
PROPANE		Asphyxiating	Asphyxiating.	Asphyxiating	Asphyxiating.	

WEL = Workplace Exposure Limit.

Ingredient Comments

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

### 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Typical
Odour	Characteristic.
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

# H16 NILCO FOAMING GLASS CLEANER SRP 500ML

## **10.5. Incompatible materials**

## **10.6. Hazardous decomposition products**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### **11.1. Information on toxicological effects**

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

#### Eye contact

Irritating to eyes. May cause chemical eye burns.

#### Route of entry

Inhalation. Skin and/or eye contact.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

### **12.1. Toxicity**

### **12.2. Persistence and degradability**

### **12.3. Bioaccumulative potential**

### **12.4. Mobility in soil**

### **12.5. Results of PBT and vPvB assessment**

### **12.6. Other adverse effects**

## **SECTION 13: DISPOSAL CONSIDERATIONS**

### **13.1. Waste treatment methods**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## **SECTION 14: TRANSPORT INFORMATION**

### **14.1. UN number**

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### **14.2. UN proper shipping name**

Proper Shipping Name                      AEROSOLS

### **14.3. Transport hazard class(es)**

## H16 NILCO FOAMING GLASS CLEANER SRP 500ML

ADR/RID/ADN Class	2
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



### **14.4. Packing group**

ADR/RID/ADN Packing group	Not Applicable
IMDG Packing group	Not Applicable
ICAO Packing group	Not Applicable

### **14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

### **14.6. Special precautions for user**

EMS F-D, S-U

### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

## SECTION 15: REGULATORY INFORMATION

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

Control of Substances Hazardous to Health.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

### **15.2. Chemical Safety Assessment**

## SECTION 16: OTHER INFORMATION

Revision Date	10/11/2015
Revision	2
Supersedes date	29/09/2015

## H16 NILCO FOAMING GLASS CLEANER SRP 500ML

### Risk Phrases In Full

R12	Extremely flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R11	Highly flammable
R36/38	Irritating to eyes and skin.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

### Hazard Statements In Full

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H332	Harmful if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.