



Brake Cleaner

James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK

Tel: 0161 627 0101 Fax: 0161 627 0971

www.addituk.com

AIBC

1. Introduction

A highly volatile, fast drying solvent based heavy duty degreaser designed to remove dust, greases and oils from automotive components

2. Where to use

On all functional components in automotive brake or clutch assemblies, including callipers, discs, clutch plates etc.

3. Where not to use

- On decorative substrates, where coatings may be affected
- On plastics or rubber components.

4 Benefits

- Powerful spray, fast evaporating formula
- Cleans Brake and clutch parts without the need for dismantling
- Dissolves and removes brake fluid, grease, oil and dust
- Eliminates brake squeal.
- Eliminates clutch slip caused by contaminated components.

5. Physical properties.

Appearance	Clear water white aerosol mist with a characteristic organic odour and extremely fast drying properties.
pH	Not applicable, non-aqueous.
Specific Gravity	0.705 – 0.720 [Base Component]
Non Volatiles % m/m	<0.05
Active Content % m/m	100
Flammability	Extremely flammable, flash point below -20°C
Composition Data, descriptive	A blend of low boiling point hydrocarbons, ketone and alcohol solvents propelled by a hydrocarbon blend.

6. Application Details.

Place a drip tray underneath the work area. Shake Well. Hold can upright. Spray liberally onto the surface to be treated, and allow contaminated liquid to drain into the tray. Agitation with a brush will assist in the removal of heavy or stubborn contamination. Flush spray until all contamination has been removed, and wipe away excess with a soft clean cloth. Always work under well ventilated conditions, taking care to avoid vapour inhalation.

7. Availability

500ml Aerosols.

B07650F, RJB, March 2012