



Clear Grease

AICL

James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK

Tel: 0161 627 0101 Fax: 0161 627 0971

www.addituk.com

1. Introduction

A colourless, multi purpose grease with strong adhesive properties and high mechanical strength designed for high speed, high stress applications providing resistance to “fling-off” through centrifugal force.

2. Where to use

On all moving metal parts, to improve slip; to maintain freedom from malfunction and seizure, and on anyother metallic components particularly gears, chains, conveyors etc.

3. Where not to use

- No restrictions

4 Benefits

- Long lasting lubrication.
- Resists corrosion.
- Suitability on vertical and inverted surfaces.
- High mechanical strength.
- Contains a PTFE for improved lubricity.
- Contains extreme pressure additive for high load bearing resistance.
- Silicone free.

5. Physical properties.

Appearance	A turbid, pale straw aerosol jet spray with a strong hydrocarbon odour.
pH	Not applicable
Specific Gravity	0.78 – 0.80 [Base]
Non Volatiles % m/m	27 - 33
Active Content % m/m, as supplied	55 – 65
Flammability, as supplied	Extremely Flammable, flash point below -20°C
Composition Data, as supplied	A solution of mineral oil, high viscosity synthetic tackifiers and lubricants, extreme pressure additive, and colloidal PTFE in an aliphatic hydrocarbon solvent and a hydrocarbon propellant.
Volatile Organic Content as supplied	Compliant with EU Directive 2004/42/CE
Service Temperatures	Up to 100°C
Application Temperatures	15 - 25°C

6. Application Details

Shake thoroughly prior to use. Spray directly onto the component from a distance of 15 to 30cm. This product is a thin liquid which dries to give a viscous tacky colourless film.

7. Availability

500ml Aerosols

B07776N, RJB, March 2012