



Diesel Treatment

AIDT300

James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK

Tel: 0161 627 0101 Fax: 0161 627 0971

www.addituk.com

1. Introduction

A solvent based fuel additive for commercial and private diesel engines.

2. Where to use

In diesel engines, in multiples of 1 x 300ml pack for each 60 litres of fuel. This product is suitable for use in all diesel engines, up to and including Euro 5, and is fully compatible with catalytic converters and particulate traps.

3. Where not to use

- Gasoline engines.

4. Benefits

- Improves fuel economy
- Reduction in noxious exhaust emissions.
- Improves engine performance. Nominal 2.0 – 3.0 Cetane boost.
- Improves low temperature starting.
- Prevents fuel system corrosion.
- Lubricates fuel injectors and pumps.
- Controls fuel oxidation deposits, gum, varnish and acids formation.
- Controls EGR [exhaust gas recirculation] valve deposits.
- Restores injector spray patterns.
- Provides anti-corrosion properties.
- De-foaming performance.
- Prevention of aqueous emulsions.

5. Physical properties.

Appearance	Pale straw free flowing liquid with a characteristic hydrocarbon odour.
pH	Not applicable, non-aqueous.
Specific Gravity	0.812 +/-0.015
Active Content % m/m	5 – 10.
Flammability	Not classified as flammable.
Composition Data	A blend of detergents and other functional components in a hydrocarbon base.

6. Application Details

Add the complete contents of the bottle to the gasoline tank, preferably, but not essentially, when filling, to allow optimum dispersion. The contents should be used for full tank contents of 60 litres, but addition to 40 litres or more will not harm combustion and still provide stipulated benefits. Application to tank contents less than 40 litres is not recommended.

7. Availability

300ml induction heat sealed PVC container with a child resistant closure.

B098425, RJB, April 2013.