



Multi Lube

AIML

James Briggs ITW Ltd
Salmon Fields, Royton, Oldham OL2 6HZ UK
Tel: 0161 627 0101 Fax: 0161 627 0971
www.addituk.com

1. Introduction

A multi purpose product with lubricating, cleaning, dewatering, penetrating and corrosion inhibition properties.

2. Where to use

On all ferrous metals, as a general purpose lubricant specifically designed to release seized and corroded components, as a general purpose lubricant, a dewatering fluid or as a temporary anti-corrosive coating.

3. Where not to use

- No restrictions

4. Benefits

- Long lasting lubrication.
- Moisture displacement.
- Moisture repellency.
- Formation of a temporary anti-corrosive coating.
- Ability to penetrate rust and corrosion deposits.
- Enhanced operating temperature range
- Contains PTFE for improved lubricity and load bearing resistance.

4. Physical properties. [Lubricant base except where stated]

Appearance	A turbid pale straw liquid with a pleasant odour.
pH	Not applicable
Specific Gravity	0.795 – 0.81
Non Volatiles % m/m	70 - 90
Active Content % m/m, as supplied	20 - 30
Viscosity	Thin liquid
Flammability, as supplied	Extremely flammable, flash point below -20°C.
Composition Data, as supplied	A solution of naphthenic oil, modified grease, water displacing additives and wetting agents, and PTFE in naphtha [petroleum], hydrocarbon heavy, in butane/isobutane/propane propellant.
Service Temperature [Continuous]	Up to 80°C
Service temperature [Intermittent]	Up to 150°C

6. Application Details

Shake thoroughly before use. Spray directly onto the component or surface, from a distance of 15 to 25cm, and allow to penetrate or form a film.

7. Availability

500ml. aerosols.

B05005A, RJB, April2012.