



## FOAMING TYRE DRESSING

### James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK  
Tel: 0161 627 0101 Fax: 0161 627 0971  
www.jamesbriggs.co.uk

APFTD500

#### 1. Introduction

A high quality foaming silicone treatment designed primarily to protect and revive the natural appearance of pre-cleaned automotive tyres.

#### 2. Where to use

This product is designed for use on the sidewalls of all domestic and commercial automotive road and off-road tyres.

#### 3. Where not to use

- On motorcycle or pedal cycle tyres.
- On tyre treads

#### 4. Benefits

- Simplicity of use, spray and leave.
- Durable silicone finish
- Helps reduce surface cracking of sidewalls

#### 5. Physical properties [Tyre and Rubber Dressing base except where stated].

Appearance	Free flowing milky white fluid
pH [10% aqueous solution]	9.0 – 11.0
Specific Gravity	0.98 – 1.00
Viscosity	Low viscosity
Non Volatiles % m/m	25 – 35
Active Content % m/m, as supplied	20 - 30
Flammability, as supplied	Extremely Flammable, flash point below -20°C
Composition Data, as supplied	An aqueous emulsion of silicone fluids and anti corrosive additives dispersed in a butane/propane/isobutane propellant
Application Temperature	Ambient temperatures

#### 6. Application Details

Shake the can thoroughly before use and apply to the sidewalls only from a distance of 10 – 15 cm. Allow a few minutes for the foam to subside.

If a higher level of shine is required, wipe the initial application with a soft lint free cloth and apply a second application.

Avoid spraying onto the tyre tread. Take care to avoid accidental application to brake equipment and test brakes prior to full use of vehicle. Accidental overspray may be removed with a wet cloth.

#### 7. Availability

500ml Aerosols

B077514 February 2013